

# HARDWARE SPECIFICATIONS

UPDATED - March 2020

## 1. Database Server

Component / Number of users	1–10 users	11–25 users	26–50 users	51–99 users	100+ users
Processor – Recommended*	4 Cores @1.6 GHz+	8 Cores @1.6 GHz+	8 Cores @2.26 GHz+	8 Cores @2.26 GHz+	16 Cores @2.26 GHz+
Processor – Minimum*	2 Cores @1.6 GHz+	4 Cores @1.6 GHz+	4 Cores @1.6 GHz+	4 Cores @1.6 GHz+	8 Cores @1.6 GHz+
Single Thread score of Processor <sup>#</sup>	1450 or above	1450 or above	1450 or above	1450 or above	1450 or above
Memory / RAM – Recommended	16 GB (frequency: DDR4 - 2933)	32 GB (frequency: DDR4 - 2933)	64 GB (frequency: DDR4 - 2933)	64–128 GB (frequency: DDR4 - 2933)	128–160 GB (frequency: DDR4 - 2933)
Memory / RAM – Minimum	8 GB (frequency: DDR4 - 2400)	16 GB (frequency: DDR4 - 2400)	32 GB (frequency: DDR4 - 2400)	64 GB (frequency: DDR4 - 2400)	128 GB (frequency: DDR4 - 2400)
Disk Configuration	<ul style="list-style-type: none"> <li>RAID level 1+0 is recommended for optimal performance</li> <li>Minimum required is RAID level 5</li> </ul>				
Hard Drive – Total Storage (Should be capable of adding more storage)	500 GB SSD SAS-3 (12 Gbps)	1 TB SSD SAS-3 (12 Gbps)	1.5 TB SSD SAS-3 (12 Gbps)	2 TB SSD SAS-3 (12 Gbps)	3 TB SSD SAS-3 (12 Gbps)
	<ul style="list-style-type: none"> <li>Recommended Storage for IMS Database drive - PCIe NVMe 3.0 SSD</li> </ul>				
Operating System	<ul style="list-style-type: none"> <li>Windows® Server 2012 Standard</li> <li>Windows® Server 2016</li> </ul>				
Network Adapter (1 Gbps)	2 Adapter	2 Adapter	4 Adapter	4 Adapter	4 Adapter
Internet Connectivity	<ul style="list-style-type: none"> <li>The server must be connected to the Internet via a high-speed Internet connection (minimum 10 Mbps).</li> </ul>				
<b>Notes</b>	<ul style="list-style-type: none"> <li>This server should only host IMS software database server.</li> <li>To match HIPAA compliance requirements, you can choose any disk encryption method supported by Microsoft Windows Operating Systems.</li> </ul>				

# HARDWARE SPECIFICATIONS

UPDATED - March 2020

## 2. Citrix/2X/Terminal Server (for remote connections)

Component / Number of users	1–10 remote users	11–25 remote users	26–50 remote users	51–99 remote users	
Processor – Recommended*	8 Cores @1.6 GHz+	8 Cores @2.26 GHz+	8 Cores @2.26 GHz+	16 Cores @2.26 GHz+	
Processor – Minimum*	4 Cores @1.6 GHz+	4 Cores @1.6 GHz+	8 Cores @1.6 GHz+	8 Cores @2.26 GHz+	
Single Thread score of Processor#	1450 or above	1450 or above	1450 or above	1450 or above	1450 or above
Memory / RAM – Recommended	16 GB DDR4 - 2933	32 GB DDR4 - 2933	64 GB DDR4 - 2933	128 GB DDR4 - 2933	
Memory / RAM – Minimum	12 GB DDR4 - 2400	24 GB DDR4 - 2400	48 GB DDR4 - 2400	96 GB DDR4 - 2400	
Disk Configuration	<ul style="list-style-type: none"> <li>RAID level 1+0 is recommended for optimal performance</li> <li>Minimum required is RAID level 5</li> </ul>				
Hard Drive – Total Storage (Should be capable of adding more storage)	160 GB SSD SAS-3 (12 Gbps)	250 GB SSD SAS-3 (12 Gbps)	320 GB SSD SAS-3 (12 Gbps)	500 GB SSD SAS-3 (12 Gbps)	
Operating System	<ul style="list-style-type: none"> <li>Windows® Server 2012 Standard (along with Terminal Server and Client Access License) or</li> <li>Windows® Server 2016</li> </ul>				
Network Adapter (1 Gbps)	2 Adapter	2 Adapter	4 Adapter	4 Adapter	
Internet Connectivity	<ul style="list-style-type: none"> <li>For Remotely Hosted Terminal Servers :The basic requirement is at least 2MB download per user, but scanning and imaging workstations require greater bandwidth.</li> </ul>				

**+Note:**

- **The cores mentioned here are physical cores.**
- **If the server is based on virtual environment, consider the following factors for configuring the servers:**
  - Number of physical processor/core vs virtual core assigned
  - Number of other VM that are setup on the same host
- **We do not recommend excessive virtual cores on actual physical processor**

#You can check the single-thread score of the CPU using the following link. <https://www.cpubenchmark.net/singleThread.html>

## HARDWARE SPECIFICATIONS

UPDATED - March 2020

### 3. Web Applications Server

Component	Minimum Specifications
Processor	Quad-core (4 cores, 1.6 GHz+ or later)
Memory / RAM	8 GB
Hard Drive	80 GB
Operating System	<ul style="list-style-type: none"> <li>• Windows® Server 2012 Standard</li> <li>• Windows® Server 2016</li> </ul>
Internet Connectivity	<ul style="list-style-type: none"> <li>• Broadband Internet connection (10Mbps)</li> <li>• Static IP address</li> <li>• Port 80 and 443 should be open</li> </ul>
Network Adapter	2 Adapter
Sybase License	1 Sybase license is required to allow Web Server to connect to IMS DB server

# HARDWARE SPECIFICATIONS

UPDATED - March 2020

## 4. Workstations

Component	Minimum Specifications	Recommended Specifications*
Processor	Intel® i5, 2.70 GHz+	Intel® i7, 2.40 GHz+
Memory / RAM	4 GB	8 GB
Hard Drive	120 GB	250 GB SSD
Operating system	Windows 8 / Windows 10	
Wired Network	1000 Mbps Ethernet or higher	1000 Mbps Ethernet or higher
Wireless (Wi-Fi)	802.11G or higher	802.11N or higher
Router / Firewall	Secure encrypted connectivity for communication between facilities is required using an IPsec VPN enabled router.	
Ports	The following ports are used for sending and receiving claims through IMS. <ul style="list-style-type: none"> <li>• ENS Professional: 3566</li> <li>• ENS Institutional: 22</li> <li>• AVAILITY: 9922</li> <li>• REALMED: 22</li> </ul>	

\*We do not support Operating systems below Window 8 and Window 2012 server Edition for Workstation and Server.

\*Recommended for workstations using services like scanning, Dragon dictation, Word Processing, hardware interfaces etc.

The following factors can impact system performance:

- Firewall/antivirus software (even if virus scan is not running, it will scan each file that is downloaded and opened or scanned and saved)
- Insufficient RAM memory
- Hard drive encryption
- Multiple network hops
- Slow network / more traffic on network
- Low space on system partition or working partition
- Background process for services like backup and monitoring.
- Absence of proper system maintenance.

# HARDWARE SPECIFICATIONS

UPDATED - March 2020

## 5. Peripheral Hardware Specifications

<b>Printers</b>	
Printer	<ul style="list-style-type: none"> <li>PCL5 - compatible network printer (All-in-one devices should not be used as a scanner but can be used for printing.)</li> </ul>
Label Printer	<p>Zebra ZD410</p> <ul style="list-style-type: none"> <li>Over the RDP/2x/Citrix sessions, it is mandatory that printer redirects through manufacturer's driver.</li> <li>If not using manufacturer's driver then TS Printer is required for proper printer redirection over the remote session.</li> </ul>
CHDP Printer	Windows compliant laser printer. We recommend the OKI MICROLINE® 420 (This unit can work on multiple drivers. Install IBM Pro printer roman 3 drivers. We recommend this for a busy practice.)
Rx Printers	Brother LaserJet 2170N network printer (to use with non-padded Rx scripts), if you would like to print Rx pads.
<b>Display Devices</b>	
Resolution	Minimum required resolution of the display devices is 1366x768
<b>Scanners and Imaging</b>	
Scanner	Any Twain-compatible scanner is compatible with IMS
Card scanner	<p>DocketPORT DS687 - Duplex</p> <p>DocketPORT PS467 - Simplex</p>
Barcode scanner	Any plug-n-play barcode scanners

# HARDWARE SPECIFICATIONS

UPDATED - March 2020

Signature pad	<p>For use with locally hosted server:</p> <ul style="list-style-type: none"> <li>• Topaz model: T-LBK755SE-BBSB-R</li> <li>• Topaz model: T-LBK755SEBH or T-LBK750SEBH</li> <li>• Topaz SignatureGem SE 4X5</li> <li>• Topaz SignatureGem SE 4X3</li> <li>• Topaz SignatureGemSE 4X3 TM-LBK755-BHSB</li> </ul> <p>For use with remotely hosted server:</p> <ul style="list-style-type: none"> <li>• Topaz model: T-LBK755SE-BBSB-R</li> <li>• Topaz model: T-LBK755SEBH and the T-LBK750SEBH</li> <li>• Requires serial cable kit. Topaz part number A-CSA4-2</li> </ul> <p>Note:</p> <ul style="list-style-type: none"> <li>• If you disconnect the signature pad from its USB power port, reconnect it to the same USB power port.</li> </ul>
Web camera	Any Plug-n-Play webcam, USB 2.0 or higher
<b>Medical devices</b>	
Vital Signs	Welch Allyn – Spot Vital Signs – Lxi Midmark
FeNO (Fractional Nitric Oxide)	Niox Device
Laser Device and Advanced Image analysis system	Hamilton Thorne
EKG	Midmark
Immunoassay Analyzer	<ul style="list-style-type: none"> <li>• Immulite 1000</li> <li>• Immulite 2000 XPi</li> <li>• Roche Cobas e411</li> <li>• Tosoh AIA - 360</li> <li>• Tosoh AIA - 900</li> </ul>
Spirometry	<ul style="list-style-type: none"> <li>• Midmark</li> <li>• Morgan Scientific (Spirometer model is the pneumotrac 6800 with ComPAS software)</li> </ul>
Glucose Meter Interface	IDI (Intelligent Diabetic Interface)
Ultrasound Machines	Any ultrasound machine that can generate DICOM files and have internet access
Fluoroscopic/X-ray devices	Any fluoroscopic device that can generate DICOM files and have internet access

## HARDWARE SPECIFICATIONS

UPDATED - March 2020

<b>Network</b>	
Router / Firewall	Discretion of local IT technician For better performance, we recommend Gigabyte switches and routers (10/100/1000)
Networking	Hardwiring your office to the Internet is always the best solution. However, if you seek the convenience of wireless PCs, you do have the option of using them through a Terminal Services connection to a computer that is hardwired to the Internet. Setting up a simple remote connection will give you the flexibility of wireless internet with the dependability of a hardwired Internet connection.
URLs to be whitelisted	<ul style="list-style-type: none"> <li>● services.meditab.com</li> <li>● api.medpharmservices.com</li> <li>● portal.medpharmservices.com</li> <li>● mps.auth0.com</li> <li>● *.googleapis.com</li> <li>● *.google.com</li> <li>● static.opentok.com</li> </ul>
<b>Backup</b>	
<p>You are responsible for keeping your data safe and secure. In the unfortunate event that it's compromised, data recovery may be difficult and costly. Backing up your files is the best thing that you can do to protect your office's data, safeguard your patients' information, and preserve your paperless environment. And your understanding of the backup process is crucial to successful data recovery.</p> <p>We strongly encourage that you hire an IT professional to handle your backups. Have a qualified IT technician reach out to our technical support team so that we can help you come up with a unique and customized disaster recovery plan for your office</p>	

# HARDWARE SPECIFICATIONS

UPDATED - March 2020

## 6. Minimum Computer Requirements for Midmark Devices

Item	Requirement
Operating Systems	<ul style="list-style-type: none"> <li>Windows® 10, Professional and Enterprise, 32-bit and 64-bit</li> <li>Windows® 8, Professional and Enterprise, 32-bit and 64-bit</li> <li>Windows® 7, Professional and Enterprise, 32-bit and 64-bit</li> </ul>
Hardware Requirements	Windows® compatible personal computer
CPU	Intel® Core™2 Duo Processor E4300 (2M Cache, 1.80 GHz, 800 MHz FSB) (x86) or 64-bit (x64) processor or faster
Disk	2 GB of free disk space or greater
Memory	Minimum 2 GB of system memory
Input/Output Ports	Number of USB and Serial Ports required depends on the type of IQ digital devices to be connected to. Please refer to the specific product specifications.
Pointing Device	Windows® compatible mouse
Keyboard	Windows® compatible keyboard
Display	1024x768 or higher resolutions for the real time acquisition screen 16-bit color Wide-screen (1680x1050) is highly recommended

- **In a Client/Server environment, the following are required:**
- A network with at least one Windows NT Server, version 4.0 or later
  - Microsoft SQL Server installed on the NT Server
  - Client computers (running Windows® 8 or 7)
  - Familiarity with the Microsoft SQL Server product

[Click here](#) for Ancillary Services Prerequisites

[Click here](#) for SaaS-Based System Hardware Specifications